

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
29 March 2001 (29.03.2001)

PCT

(10) International Publication Number
WO 01/22543 A1

(51) International Patent Classification⁷: H01S 5/10, 5/40

(21) International Application Number: PCT/IE00/00110

(22) International Filing Date:
25 September 2000 (25.09.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
S990793 23 September 1999 (23.09.1999) IE

(71) Applicant (for all designated States except US): THE
PROVOST, FELLOWS AND SCHOLARS OF THE
COLLEGE OF THE HOLY AND UNDIVIDED
TRINITY OF QUEEN ELIZABETH NEAR DUBLIN
[IE/IE]; Dublin 2 (IE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): O'GORMAN,

James, Christopher [IE/IE]; 9 Portersgate Rise, Clonsilla,
Dublin 15 (IE). MCEVOY, Paul [IE/GB]; 8 Tennyson
Court, Royston, Hertfordshire SG8 5SZ (GB). MCDON-
ALD, David [IE/IE]; 17 Drummartin Park, Dundrum,
Dublin 14 (IE). LOGUE, Frederick, Paul [IE/IE];
Whitecross, Julianstown, County Meath (IE). LANDAIS,
Pascal, Michel [FR/IE]; 3 Hatch Place, Dublin 2 (IE).


(74) Agent: F.F. GORMAN & CO.; 54 Merrion Square,
Dublin 2 (IE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,
DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,
LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,
NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM,
TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian

[Continued on next page]

(54) Title: AN OPTICAL WAVEGUIDE AND A METHOD FOR PROVIDING AN OPTICAL WAVEGUIDE



(57) Abstract: A laser diode (1) having an optical path (15) defined in an active layer (2) which is sandwiched between a substrate layer (3) and a top layer (4) and defined by a ridge (14) formed in the top layer (4) outputs laser light of a single predetermined wavelength. Refractive index altering grooves (21) extending transversely in the top layer (4) are provided at spaced apart locations for altering the refractive index of the active layer (2) along the optical path at partial reflecting locations (20) for causing partial longitudinal reflections of the laser light generated in the optical path (15) so that standing waves or harmonics thereof of the single predetermined wavelength are set up between the respective partial reflecting locations (20) and a first mirror facet (8) in the optical path (15). In order that the standing waves set up between the partial reflecting locations (20) and the first mirror facet (8) are harmonics of

the predetermined single wavelength, the refractive index altering grooves (21) are located along the ridge (14) for forming the reflecting locations (20) at distances from the first mirror facet (8) which correspond to the effective length of the optical path (15) resulting from the affect of the inclusion of the reflecting locations (20) rather than at locations corresponding to the actual length of the light path (15).

WO 01/22543 A1



patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *With international search report.*